

ADVANCED POWER SYSTEMS INTERNATIONAL INC.

18 Hemlock Drive
New Hartford, CT 06057
860-921-0009

Website – www.fitchfuelcatalyst.com



**2015 VW Golf GTI 2.0 liter
Fitch Model: F3624**



1. Remove the engine cover by lifting gently on each corner.
2. Relieve the pressure from the fuel system by using a pair of pliers to disconnect the line from the fuel pump on the right side of the engine bay with a red square box in the picture, be careful this line is under pressure, put a towel around the line as you pull the line off after squeezing and sliding the clamp back a few inches.



Fitch
mounting
location

3. Locate the high pressure fuel line in the upper left portion of the engine bay by tracing the line that just was removed from the fuel pump all the way back to the back left of the engine bay.
4. Put a towel around the line to catch any spilled fuel, disconnect the high pressure fuel line connector. Push the rubber line into the metal line while squeezing the connectors then pull back disconnecting the OEM line.





5. Put plastic protection covers over the lines of the Fitch Fuel Catalyst then route the lines between the engine mount and the strut tower brace on the passenger side of the engine bay. Be careful to make sure no exposed line touches the a/c components. (Note: customer may have to supply own plastic line covers or heat tape to wrap the fuel lines)



8. Reattach the fuel line to the fuel pump on the right side of the engine bay, slide clamp back into its original location.

